# **FABRICATED HOLLOW STRUCTURAL SECTIONS**

ATLAS TUBE, A DIVISION OF ZEKELMAN INDUSTRIES



Atlas Tube can produce round, square and rectangular sizes in the largest size range in North America



Atlas Tube was founded in 1984 and ever since has been growing and innovating to become the largest producer of Hollow Structural Sections in North America. As part of the Zekelman Industries family of companies, Atlas Tube is an integral part of the structural steel supply chain, serving the needs of Architects, Engineers, Fabricators, Contractors and Service Centers, by providing the largest size range in the industry and unmatched technical support.

The North American steel industry is the cleanest of all the major steel producing areas of the world. Of the seven largest steel producing countries, the U.S. has the lowest CO2 emissions per ton of steel produced and the lowest energy intensity (AISI, 2021). Atlas is committed to maintain this fact by constantly improving our processes. For more information about Atlas Tube and the products we offer, please visit www.atlastube.com.





According to ISO 14025 and ISO 21930:2017

ATLAS TUBE FABRICATED HOLLOW STRUCTURAL SECTIONS

EPD PROGRAM AND PROGRAM OPERATOR NAME, ADDRESS, LOGO, AND WEBSITE	UL Environment 333 Pfingsten Road Northbrook, I	l 60611	https://www.ul.com https://spot.ul.com			
GENERAL PROGRAM INSTRUCTIONS AND VERSION NUMBER	General Program Instructions v.2.5 March 2020					
ASSOCIATION NAME AND ADDRESS	Atlas Tube, 1855 East 122 <sup>nd</sup> Stree	Atlas Tube, 1855 East 122 <sup>nd</sup> Street, Chicago, Illinois 60633				
DECLARATION NUMBER	4790050508.101.1					
DECLARED PRODUCT & DECLARED UNIT	Fabricated Hollow structural steel	sections, 1 metric ton				
REFERENCE PCR AND VERSION NUMBER	Part A: Calculation Rules for the L Environment, V3.2, 12.12.2018) a Requirements (UL Environment, V	CA and Requirements Project Report, (IB nd Part B: Designated Steel Construction /2.0, 08.26.2020).	U/UL Product EPD			
DESCRIPTION OF PRODUCT APPLICATION/USE	Fabricated Hollow structural steel	sections used in construction				
MARKETS OF APPLICABILITY	North America					
DATE OF ISSUE	March 22, 2022					
PERIOD OF VALIDITY	5 years					
EPD TYPE	Product specific					
EPD SCOPE	Cradle to gate					
YEAR(S) OF REPORTED PRIMARY DATA	2019-2020					
LCA SOFTWARE & VERSION NUMBER	GaBi v10					
LCI DATABASE(S) & VERSION NUMBER	GaBi 2021 (CUP 2021.2)					
LCIA METHODOLOGY & VERSION NUMBER	IPCC AR5 + TRACI 2.1					
		UL Environment				
The sub-category PCR review was conducted b	y:	PCR Review Panel				
		epd@ul.com				
This declaration was independently verified in a The UL Environment "Part A: Calculation Rules Requirements on the Project Report,", v3.2 (Dec ISO 21930:2017, serves as the core PCR, with a USGBC/UL Environment Part A Enhancement (	CooperMcC					
□ INTERNAL ⊠EXTERNAL	Cooper McCollum, UL Environment					
This life cycle assessment was conducted in acc reference PCR by:	cordance with ISO 14044 and the	Sphera Solutions Inc				
		1 C MAN				

This life cycle assessment was independently verified in accordance with ISO 14044 and the reference PCR by:

artes A. Mellert

James Mellentine, Thrive ESG

#### LIMITATIONS

**Environment** 

The environmental impact results of steel products in this document are based on a declared unit and therefore do not provide sufficient information to establish comparisons. The results shall not be used for comparisons without knowledge of how the physical properties of the steel product impact the precise function at the construction level. The environmental impact results shall be converted to a functional unit basis before any comparison is attempted. See the results section for additional EPD comparability guidelines.

Environmental declarations from different programs (ISO 14025) may not be comparable.







According to ISO 14025 and ISO 21930:2017

## General Information

#### **Description of Organization**

Atlas Tube is a division of Zekelman Industries which is the largest independent pipe and tube manufacturer in North America. The Atlas Tube division produces cold-formed, welded hollow structural sections (HSS) in round, square and rectangular shapes. Atlas Tube has the largest size range and produces the largest volume of HSS in the industry.

This environmental product declaration (EPD) represents hollow structural sections (HSS) produced by Atlas Tube at our facilities in Birmingham, AL, Blytheville, AR, Chicago, IL, Harrow, ON, and Plymouth, MI.

#### **Product Description**

Steel tubes covered by this product declaration are classified as either Hollow Structural Sections (HSS) or mechanical tubing. They are produced by the single seam Electric Resistance Welded (ERW) process in round, square and rectangular shapes. These products can be used in any welded or bolted construction and in various manufactured products.

#### **Product Specification**

HSS products produced by Atlas Tube are defined by the following ASTM standards.

- **ASTM A500** Standard Specification for Cold-Formed Welded and Seamless Carbon Steel Structural Tubing in Rounds and Shapes
- ASTM A847 Standard Specification for Cold-Formed Welded and Seamless High-Strength, Low-Alloy Structural Tubing with Improved Atmospheric Corrosion Resistance
- ASTM A1085 Standard Specification for Cold-Formed Welded Carbon Steel Hollow Structural Sections (HSS)
- ASTM A252 Standard Specification for Welded and Seamless Pipe Piles
- CSA G40.20/G40.21 General Requirements for Rolled or Welded Structural Quality Steel/Structural Quality Steel
- ASTM A513 Standard Specification for Electric-Resistance-Welded Carbon and Alloy Steel Mechanical Tubing





#### ATLAS TUBE FABRICATED HOLLOW STRUCTURAL SECTIONS

### Flow Diagram



#### Product Average

The 2019 and 2020 production data used in this EPD considers HSS produced by Atlas Tube during those years. The products are manufactured in five facilities located in North America. Results are weighted according to production totals at all locations based on the data. Facility-specific global warming potential results are provided in separate tables.

#### Application

Applications can be, but are not limited to, buildings, bridges, sign support structures, driven pipe piles, and any other application that requires the strength and beauty of HSS.

#### **Material Composition**

Steel HSS products are made of carbon steel with a small percentage of alloy elements included. The products do not contain any hazardous substances according to the Resource Conservation and Recovery Act (RCRA), Subtitle 3. The products do not release dangerous substances to the environment, including indoor air emissions, gamma or ionizing radiation, or chemicals released to air or leached to water and soil.

### Methodological Framework

#### **Declared unit**

Environment

The declared unit for this EPD is one metric ton of steel construction products. Note that comparison of EPD results on a mass basis alone is insufficient and should consider the technical performance of the product.



# 

Page 4

#### Table 1. Declared unit

NAME	VALUE	Unit
Declared unit	1	metric ton
Density (typical)	7,850	kg/m <sup>3</sup>

#### System Boundary

This EPD is "cradle-to-gate" in scope. The life cycle stages included in the assessment represent the product stage (modules A1-A3).

PRO	DUCT ST	AGE	CONST ION PR STA	TRUCT- OCESS AGE		USE STAGE END OF LIFE STAGE				ΞE	BENEFITS AND LOADS BEYOND THE SYSTEM BOUNDARY					
Raw material supply	Transport	Manufacturing	Transport from gate to site	Assembly/Install	Use	Maintenance	Repair	Replacement	Refurbishment	Building Operational Energy Use During Product Use	Building Operational Water Use During Product Use	Deconstruction	Transport	Waste processing	Disposal	Reuse, Recovery, Recycling Potential
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
х	Х	Х	MND	MND	MND	MND	MND	MND	MND	MND	MND	MND	MND	MND	MND	MND

\* X = module included, MND = module not declared

### Allocation

No multi-output allocation was required in the foreground system of the study.

Allocation of background data (energy and materials) taken from the GaBi 2021 databases is documented online at <u>http://www.gabi-software.com/america/support/gabi/</u>. Background data for steelmaking from AISI use the system expansion allocation method for co-products from the steelmaking process.

Since the EPD does not cover the end-of-life of the products, end-of-life allocation is outside the scope of the study. Metal scrap from manufacturing (module A3) was balanced with the scrap demand of the raw materials module (A1) in order to calculate the net scrap input to module A1.

Under a cradle-to-gate system boundary, scrap inputs to the system are not associated with any upstream burden, and scrap produced during manufacturing is assumed to be at least the same quality as scrap inputs into steelmaking. Remelting of scrap to produce structural steel and other raw materials is accounted for within module A1 using upstream datasets.

#### **Cut-off Rules**

In lieu of arbitrary cut-off criteria, all available energy and material flow data were included in the model for processes





ATLAS TUBE FABRICATED HOLLOW STRUCTURAL SECTIONS According to ISO 14025 and ISO 21930:2017

#### within the system boundary.

In cases where no matching life cycle inventories were available to represent a flow, proxy data were applied based on conservative assumptions regarding environmental impacts.

#### **Data Sources**

The LCA model was created using the GaBi 10 software system for life cycle engineering, developed by Sphera (Sphera, 2021). Background life cycle inventory data for raw materials and processes were obtained from the GaBi 2021 database (CUP 2021.1). Primary manufacturing data were provided by participating Atlas Tube.

#### **Data Quality**

A variery of tests and checks were performed by the LCA practitioner throughout the project to ensure high quality of the completed LCA. Checks included an extensive internal review of the project-specific LCA models developed as well as the background data used. A full data quality assessment is documented in the background report.

#### **Period Under Review**

Primary data were collected for HSS production during the year 2019 and 2020. Background data for steel coil production was taken from The American Iron and Steel Institute (AISI) and represents steel production during 2017. Fabrication data was taken from The American Institute of Steel Construction (AISC) and represents fabrication activity in 2019 and 2020 (AISI, 2021) (AISC, 2021). This analysis is intended to represent production in 2020.

#### **Estimates and Assumptions**

The underlying study was conducted in accordance with the PCR. While this EPD has been developed by industry experts to best represent the product system, real life environmental impacts of HSS products may extend beyond those defined in this document.

All of the raw materials and energy inputs have been modeled using processes and flows that closely follow actual production data on raw materials and processes. All of the reported material and energy flows have been accounted for. The HSS inventory data was collected as part of The Steel Tube Institute (STI) industry-average EPD (STI, 2021). Where inbound transportation data was incomplete, a distance of 500 miles by truck was used.

Proxy data were applied to some materials where no matching life cycle inventories were available, as documented in the background report.

### **Technical Information and Scenarios**

#### Manufacturing

Hollow structural sections are manufactured by cold-forming steel coil into tubes. Hot-rolled coil is first slit into sections of appropriate width. The narrower coils are then uncoiled and passed through a series of rollers that form the continuous sheet into tubes. Tube cross-sections can be square, rectangular or round. The two edges of the coil are welded together via an electric resistance welding process and the product is then cut to length. Once manufactured,





ATLAS TUBE FABRICATED HOLLOW STRUCTURAL SECTIONS According to ISO 14025 and ISO 21930:2017

HSS can be powder coated or primed—or left uncoated. The tubes are subsequently packaged for shipment.

The primary input to HSS production is the steel itself, although small amounts of process materials are needed. Electricity is used for manufacturing and to move the materials. Manufacturing produces some metal scrap. The scrap generated during manufacturing is assumed to be produced at the same quality as used by the upstream metal production processes. Therefore, the scrap from manufacturing is treated assuming open-loop recycling.

#### **Inbound Transportation**

Inbound transportation distances and modes for steel and process materials were collected from each site.

#### **Transportation**

Transportation to the customer or construction site is outside the scope of this EPD. Transportation (A2) from the HSS producers to the fabricator is included in the analysis and in this report.

#### **Product Installation**

This EPD includes fabrication impacts, however, installation (erection) is outside the scope of this EPD.

Use

Product use is outside the scope of this EPD.

Reuse, Recycling, and Energy Recovery

Product reuse, recycling, and incineration for energy recovery is outside the scope of this EPD.

#### Disposal

Product disposal is outside the scope of this EPD.

### **Environmental Indicators Derived from LCA**

North American life cycle impact assessment (LCIA) results are declared using TRACI 2.1 (Bare, 2012; EPA, 2012) methodology, with the exception of GWP which is reported using the IPCC AR5 (IPCC, 2013) methodology, excluding biogenic carbon. Primary energy use represents the lower heating value (LHV) a.k.a. net calorific value (NCV).

LCIA results are relative expressions and do not predict actual impacts, the exceeding of thresholds, safety margins or risks.

Fabrication requires 1.08 metric tons of HSS per 1 metric ton of fabricated product (AISC, 2021). A1 includes production of all 1.08 metric tons of HSS, A2 represent transportation to the fabrication facility and A3 represents the fabrication activities.



# 

### ATLAS TUBE FABRICATED HOLLOW STRUCTURAL SECTIONS

# According to ISO 14025 and ISO 21930:2017

Page 7

Table 1. LCIA results, per 1 metric ton of fabricated HSS							
PARAMETER	Unit	Total	A1	A2	A3		
GWP 100	kg CO <sub>2</sub> eq.	1.94E+03	1.80E+03	4.46E+01	9.67E+01		
ODP*	kg CFC 11 eq.	1.62E-09	-2.52E-12	8.67E-14	1.62E-09		
AP	kg SO <sub>2</sub> eq.	4.21E+00	3.87E+00	1.83E-01	1.52E-01		
EP	kg N eq.	2.23E-01	1.94E-01	1.64E-02	1.23E-02		
SFP	kg O₃ eq.	7.18E+01	6.51E+01	4.44E+00	2.23E+00		
ADP <sub>fossil</sub>	MJ surplus	1.71E+03	1.53E+03	7.16E+01	1.04E+02		

\* ODP has limited relevance due to the absence of ozone-depleting emissions in the LCI, in both the background and foreground data.

**Comparability:** Comparisons cannot be made between product-specific or industry average EPDs at the design stage of a project before a building has been specified. Comparisons may be made between product-specific or industry average EPDs at the time of product purchase when product performance and specifications have been established and serve as a functional unit for comparison. Environmental impact results shall be converted to a functional unit basis before any comparison is attempted.

Any comparison of EPDs shall be subject to the requirements of ISO 21930. EPDs are not comparative assertions and are either not comparable or have limited comparability when they have different system boundaries, are based on different product category rules or are missing relevant environmental impacts. Such comparison can be inaccurate, and could lead to erroneous selection of materials or products which are higher-impact, at least in some impact categories.

#### Table 2. Resource use results, per 1 metric ton of fabricated HSS

PARAMETER	Unit	Total	A1	A2	A3
RPRE	MJ LHV	1.23E+03	9.55E+02	6.24E+01	2.16E+02
RPRM	MJ LHV	_	_	_	-
NRPRE	MJ LHV	2.50E+04	2.28E+04	6.91E+02	1.47E+03
NRPRM	MJ LHV	1.27E+01	1.29E-01	0.00E+00	1.26E+01
SM	kg	5.26E+02	5.25E+02	0.00E+00	7.52E-01
RSF	MJ LHV	-	-	-	-
NRSF	MJ LHV	-	-	-	-
RE	MJ LHV	_	-	-	-
FW	m <sup>3</sup>	9.63E+00	8.77E+00	1.81E-01	6.82E-01





ATLAS TUBE FABRICATED HOLLOW STRUCTURAL SECTIONS

Table 3. Output flows and waste categories results, per 1 metric ton of fabricated HSS							
PARAMETER	Unit	Total	A1	A2	A3		
HWD	kg	3.33E-01	5.26E-04	0.00E+00	3.32E-01		
NHWD	kg	9.99E+00	3.33E-01	0.00E+00	9.66E+00		
HLRW	kg	9.88E-04	8.39E-04	3.16E-05	1.18E-04		
ILLRW	kg	8.26E-01	7.01E-01	2.64E-02	9.85E-02		
CRU	kg		-	-	-		
MR	kg	1.65E+02	8.81E+01	0.00E+00	7.71E+01		
MER	kg		-	-	-		
EE	MJ LHV	_	-	_	_		

To align with the PCR, "product specific EPDs which include averaging shall report the range of results for all IPCC AR5 and TRACI indicators for products included in the average." The min and max results presented in Table 4 represent the facilities with the lowest (best) and highest (worst) impacts, respectively. Min and max facilities are determined for each impact category separately. The mean and median do not take production volumes across facilities into account (i.e., it is a calculation based on each individual facility as a data point), while the weighted average presented in

Table 1 through Table 3 is calculated via production volume weightings reported by each participating facility.

#### Table 4. Statistical metrics across LCIA results, per 1 metric ton of fabricated HSS

PARAMETER	υνιτ	А1 (мім)	A1 (MAX)	MAX/MIN RATIO	A1 (MEAN)	A1 (MEDIAN)
GWP 100	kg CO <sub>2</sub> eq.	1.67E+03	1.92E+03	1.15E+00	1.77E+03	1.74E+03
ODP	kg CFC 11 eq.	-2.66E-12	-2.32E-12	8.72E-01	-2.47E-12	-2.48E-12
AP	kg SO <sub>2</sub> eq.	3.55E+00	4.21E+00	1.18E+00	3.79E+00	3.72E+00
EP	kg N eq.	1.79E-01	2.13E-01	1.19E+00	1.90E-01	1.85E-01
SFP	kg O₃ eq.	5.98E+01	7.12E+01	1.19E+00	6.38E+01	6.23E+01
ADP <sub>fossil</sub>	MJ surplus	1.44E+03	1.64E+03	1.14E+00	1.51E+03	1.48E+03

Atlas Tube's HSS product is manufactured at 5 different facilities. The results presented above represent a productionweighted average of these facilities. To understand how the GWP may vary between sites, facility-specific results are presented below.

Page 8

### 

#### ATLAS TUBE FABRICATED HOLLOW STRUCTURAL SECTIONS

#### According to ISO 14025 and ISO 21930:2017

Table 5. Facility-specific GWP100 results, per 1 metric ton of fabricated HSS							
GWP 100 (KG CO <sub>2</sub> EQ)	A1	A2	A3	Total			
Birmingham, AL	1.71E+03	4.46E+01	9.67E+01	1.85E+03			
Blytheville, AR	1.78E+03	4.46E+01	9.67E+01	1.92E+03			
Chicago, IL	1.74E+03	4.46E+01	9.67E+01	1.89E+03			
Harrow, ON	1.92E+03	4.46E+01	9.67E+01	2.06E+03			
Plymouth, MI	1.67E+03	4.46E+01	9.67E+01	1.81E+03			

#### Table 6. Facility-specific GWP100 results, per 1 metric ton of unfabricated HSS

GWP 100 (KG CO <sub>2</sub> EQ)	CRADLE-TO-GATE, MILL PRODUCT
Birmingham, AL	1.58E+03
Blytheville, AR	1.65E+03
Chicago, IL	1.62E+03
Harrow, ON	1.78E+03
Plymouth, MI	1.55E+03

### **Visualization of Life Cycle Impact Assessment**

The relative contribution of each life cycle stage to the overall cradle-to-gate impact are presented in Figure 1, while the contribution of manufacturing components are presented in Figure 2.



Figure 1: Relative contribution by life cycle stage for 1 metric ton of fabricated hollow structural sections





ATLAS TUBE FABRICATED HOLLOW STRUCTURAL SECTIONS According to ISO 14025 and ISO 21930:2017

The vast majority of potential environmental impacts is driven by the upstream burdens of steelmaking, therefore A1 is the dominant contributor across LCIA indicators.

To better understand sources of potential environmental impacts in Atlas Tube's manufacturing process, Figure 2 presents relative results for HSS manufacturing (A1 only). Potential environmental impacts for HSS manufacturing are dominated by upstream burdens of steelmaking.



Figure 2: Relative contribution by manufacturing component for 1 metric ton of un-fabricated hollow structural sections

### Interpretation

The cradle-to-gate potential environmental impacts of Atlas Tube's fabricated HSS products are driven by steel coil production and HSS manufacturing (A1).

## **Additional Environmental Information**

### **Environment and Health During Manufacturing**

Atlas Tube maintains an SDS of the product which contains specific Environmental, Health and Safety information of finished goods as it relates to local and international regulations. An SDS database is a centralized location in which recommended handling and regulatory exposure limits and recommended control measures can be found.

Atlas Tube always implements compliance focused measures with regulatory requirements in mind. A proactive





According to ISO 14025 and ISO 21930:2017

compliance approach is used as a guidance tool at all Atlas Tube facilities. Each facility is accountable and held to a proactive compliance standard.

#### **Environmental Activities and Certifications**

**Waste/Recycling:** Atlas Tube facilities generate very little hazardous waste streams. All locations are classified as being a small quantity generator or very small quantity generator. Where feasible, Atlas Tube recycles what would otherwise be deemed a waste, with a goal of diverting wastes from landfill. All facilities have a procedure in place to extend the life expectancy of coolant minimizing overall generated industrial waste while reducing the introduction of virgin coolant. Contaminants are continuously removed from the process allowing coolants to be reused in a closed loop system for an extended period of time.

**Emissions:** The process at Atlas Tube generates minimal air emissions. Rust inhibitors used are generally water based with a very low organics content. All cleaners are either water based or Federally exempt organic based materials.

**Safety:** Zekelman Industries understands that the health and safety of its teammates are critical to the success of the organization and strives to provide a safe and healthy workplace that exceeds the most established health and safety standards. Our consistent improvements to safety and health are accomplished through the integration of safety in all teammates' daily duties and responsibilities. This has resulted in a sustainable level of safety engagement, empowerment, and accountability throughout the organization.

### References

- AISC. (2021). *Environmental Product Declaration: Fabricated Hot-Rolled Structural Sections*. UL Environment. Retrieved from https://www.aisc.org/globalassets/why-steel/epd-aisc-hr-sections-2021.pdf
- AISI. (2021). Facts about American Steel Sustainability. Retrieved from https://www.steel.org/wpcontent/uploads/2021/11/AISI\_FactSheet\_SteelSustainability-11-3-21.pdf2021%2F11%2FAISI\_FactSheet\_SteelSustainability-11-3-21.pdf&clen=889481&chunk=true
- Bare, J. (2012). Tool for the Reduction and Assessment of Chemical and other Environmental Impacts (TRACI) -Software Name and Version Number: TRACI version 2.1 - User's Manual. Washington, D.C.: U.S. EPA.
- EPA. (2012). Tool for the Reduction and Assessment of Chemical and other Environmental Impacts (TRACI) User's Manual. Washington, D.C.: US EPA.
- IPCC. (2013). Climate Change 2013: The Physical Science Basis. Genf, Schweiz: IPCC.
- ISO. (2006). ISO 14040/Amd.1:2020: Environmental management Life cycle assessment Principles and framework. Geneva: International Organization for Standardization.
- ISO. (2006). *ISO 14044:2006/Amd.1:2017/Amd.2:2020 Environmental management Life cycle assessment Requirements and guidelines.* Geneva: International Organization for Standardization.





ATLAS TUBE FABRICATED HOLLOW STRUCTURAL SECTIONS According to ISO 14025 and ISO 21930:2017

- ISO. (2017). ISO 21930: Sustainability in buildings and civil engineering works -- Core rules for environmental product declarations of construction products and services. Geneva: International Organization for Standardization.
- Sphera. (2021). *GaBi LCA Database Documentation*. Retrieved from Sphera Solutions, Inc.: http://www.gabi-software.com/america/support/gabi/
- STI. (2021). *Steel Tube Institute.* Retrieved from https://steeltubeinstitute.org/wp-content/uploads/2021/09/7.31.21-STI\_Industry-Wide-EPD\_Hollow-Structural-Steel-Sections.pdf
- UL Environment. (2018). Part A: Life Cycle Assessment Calculation Rules and Report Requirements, Version 3.2.
- UL Environment. (2020). Part B: Designated Steel Construction Product EPD Requirements.
- UL Environment. (2020). Program Operator Rules v 2.5.

### **Contact Information**

#### Study Commissioner



Atlas Tube, a division of Zekelman Industries 1855 East 122<sup>nd</sup> Street Chicago, Illinois 60633 <u>www.atlastube.com</u>

#### **LCA Practitioner**



Sphera Solutions, Inc. 130 E Randolph St, #2900 Chicago, IL 60601 <u>https://sphera.com/contact-us/</u> <u>www.sphera.com</u>

